

JACKHAMMER Safe Operating Procedure Updated October 19, 2022 Page 1 of 1

Hazards	moving, rotating and sharp parts; dust and fumes; high pressure air hose couplings; pinch and squash; slips, trips and falls; loss of control; excessive noise; ejected material; eye injuries
Tools/Equipment	
Employee Group(s)	Facilities Management - Carpentry

Required PPE:















Safety Shoes

Protection

Protection

Protective Suit

Suit Res

Respirator

Gloves

Hard Hat

SAFE WORK PRACTICES

- Do not perform the procedure or operate the equipment until you have been appropriately trained and authorized to do so by your supervisor.
- Inspect required personal protective equipment (PPE) and replace if required.
- Do not wear loose-fitting clothing, dangling jewelry, rings, etc.
- Ensure your work area is safe well-lit, with no flammable liquids, gases or dust.
- Establish an exclusion zone with barricading and appropriate safety signage.
- Establish the location of all underground utilities.
- Be aware that this power tool is designed to create severe vibration. The hands, arms and legs will quickly tire. Take regular breaks.
- Be aware of common overuse injuries i.e., hearing loss and back pain.
- Never operate on a continuous or repetitive basis. Always take multiple breaks.
- Inspect the equipment for any obvious mechanical defects.
- Ensure all components, attachments and guards are secure before starting.
- Know the best way to do the job. Review any operational procedures.

PROCEDURE

- 1. Always use two hands. Ensure you have a firm footing and are ready to handle any reaction from the tool.
- 2. Operators should be ready to brace themselves against the high level of torque exerted by the tool
- 3. Apply slight pressure on the tool. Pressing very hard will not increase efficiency.
- 4. Stop operation if the tool bounces around uncontrollably.
- 5. Do not touch the bit immediately after operation. It may be extremely hot.
- 6. Do not operate this power tool at no-load unnecessarily.
- 7. To stop, release the handle grip switch. Turn off and disconnect after use.
- 8. Never leave this power tool unattended.
- 9. Leave the power tool in a safe, clean and tidy state.
- 10. Stow away correctly. Remove any barricading and safety warning signature.